

## 4-Way Cassette Type Free Match Indoor Units Ecodesign- Technical specifications

Model			GKH(12)BB-K6DNA3A/I	GKH(18)BB-K6DNA3A/I	GKH(24)BC-K6DNA4A/I
Function					
Capacity	Cooling	Btu/h	11900	15400	24200
	Heating	Btu/h	13600	17100	27300
Power Supply		Ph,V,Hz	1Ph,220~240V,51Hz	1Ph,220~240V,51Hz	1Ph,220~240V,51Hz
Air flow Volume		m³/h(SH/H/MH/M/ML/L/SL)	650/560/520/450	710/670/590/450	1280/1220/1100/880
		CFM(SH/H/MH/M/ML/L/SL)	382.525/330/306/265	417.835/394/347/265	753.28/718/647/518
Sound Pressure Level		dB(A) (H/L/M)	44/41/38/34	47/45/41/35	47/45/41/36
Connecting Pipe		Gas	mm	9.52	16
		Liquid	mm	6	9.52
Main Body	Dimension (WXDXH)	Outline	mm	596×596×240	840×840×240
		Package	mm	778×738×300	963×963×325
	Net Weight/Gross Weight		Kg	20.0/24.0	26.0/32.0
Panel	Dimension (WXDXH)	Outline	mm	670×670×50	950×950×60
		Package	mm	763×763×105	1033×1038×133
	Net Weight/Gross Weight		Kg	3.5/5	7/11
Loading Quantity		20'GP	sets	147	84
		40'GP/40'HQ	sets	329/376	168/192