

Fresh Air Processing Duct GMV5 – Technical Specifications

MODEL		GMV-NX140P/A(X1.2)-K		GMV-NX224P/A(X2.0)-M		GMV-NX280P/A(X2.5)-M		GMV-NX280P/A(X3.0)-M		GMV-NX450P/A(X4.0)-M	
Capacity	kW	14,00	10,00	22,40	16,00	28,00	20,00	28,00	20,00	45,00	32,00
Capacity	Btu/h	47.768	34.12	76.429	54.592	95.536	68.24	95.536	68.24	153.54	109.184
Power Supply	V-Ph-Hz	220-240V ~ 1N – 50 Hz		380-415V ~ 3N – 50 Hz		380-415V ~ 3N – 50 Hz		380-415V ~ 3N – 50 Hz		380-415V ~ 3N – 50 Hz	
Air Flow Volume (H/M/L)	m ³ /h	1.2		2		2.5		3		4	
Sound Pressure Level	dB(A)	42		47		48		51		52	
Available ESP	Pa	150		200		200		200		200	
Diameter Liquid-Gas Connection Pipe	inch	3/8" – 5/8"		3/8" – 7/8"		3/8" – 7/8"		3/8" – 7/8"		1/2" – 1 1/8"	
Unit Dimension LxHxD/ Weight	mm/kg	1463x300x756 / 63,5		1500x500x1000 / 130		1500x500x1000 / 134		1500x500x1000 / 134		1700x650x1100 / 190	