

Model		GMV-ND56PHS/A-T		GMV-ND63PHS/A-T		GMV-ND71PHS/A-T		GMV-ND80PHS/A-T		GMV-ND90PHS/A-T		GMV-ND100PHS/A-T	
Capacity	kW	5,6	6,3	6,3	7,1	7,1	8	8	9	9	10	10	11,2
Capacity	Btu/h	19107,2	21495,6	21495,6	24225,2	24225,2	27296	27296	30708	30708	34120	34120	38214,4
Power Supply	V-Ph-Hz	220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz	
Air Flow Volume (H/M/L)	m ³ /h	1000/800/600		1000/800/600		1100/900/700		1100/900/700		1700/1450/1100		1700/1450/1100	
Sound Pressure Level	dB(A)	44/40/36		44/40/36		45/41/37		45/41/37		46/44/42		46/44/42	
Available ESP	Pa	100		100		100		100		100		100	
Diameter Liquid-Gas	inch	3/8" – 5/8"		3/8" – 5/8"		3/8" – 5/8"		3/8" – 5/8"		3/8" – 5/8"		3/8" – 5/8"	
Connection Pipe													
Unit Dimension LxHxD/ Weight	mm/kg	1271x558x268 / 35		1271x558x268 / 35		1271x558x268 / 35		1271x558x268 / 35		1229x775x290 / 47		1229x775x290 / 47	

Model		GMV-ND112PHS/A-T		GMV-ND125PHS/A-T		GMV-ND140PHS/A-T		GMV-ND160PHS/A-T		GMV-ND224PH/A-T		GMV-ND280PH/A-T	
Capacity	kW	11,2	12,5	12,5	14	14	16	16	17	22,4	25	28	31
Capacity	Btu/h	38214,4	42650	42650	47768	47768	54592	54592	58004	76428,8	85300	95536	105772
Power Supply	V-Ph-Hz	220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz	
Air Flow Volume (H/M/L)	m ³ /h	1700/1450/1100		2000/1550/1200		2000/1700/1400		2650/		4000		4400	
Sound Pressure Level	dB(A)	46/44/42		48/45/42		48/46/44		50/48/46		54/50/45		55/50/45	
Available ESP	Pa	100		100		100		100		200		200	
Diameter Liquid-Gas	inch	3/8" – 5/8"		3/8" – 5/8"		3/8" – 5/8"		3/8" – 5/8"		3/8" – 3/4"		3/8" – 7/8"	
Connection Pipe													
Unit Dimension LxHxD/ Weight	mm/kg	1229x775x290 / 47		1229x775x290 / 47		1229x775x290 / 47		1340x750x350 / 60		1483x791x385 / 82		1686x870x450 / 105	